

plank.

Australian hardwood Blackbutt



Colour and grain



Product details	Species	Blackbutt
	Construction	Multi-layered engineered
	Format	Straight
	Profile	Clip lock
	Edge profile	Micro bevelled
	Coating	WOCA UV oil
	Grade	Signature
	Texture	Wire-brushed
	Nested boards	25%
	Pack size	1.516 m²
	Warranty	25 years structural
	Maintenance	Refer to our care and maintenance manual

Dimensions and profile	Construction	Dimensions
	3 mm veneer 	133 × 1900 × 14 mm

Technical criteria	Species origin	Australia (contact for more information)
	Janka hardness rating	9.1 kN
	Moisture content	8–10%
	Density	0.75 g/cm²
	Total VOC emissions	0.011 mg/m²/hr
	Formaldehyde emissions	E1 0.007 mg/m²/hr
	Pentachlorophenol emission	<5 PPM (no Pentachlorophenol containing materials are used)
	Slip testing	P3
	Wet pendulum test	P3
	European fire classification	Dfl-s1
	Reaction to fire; floors (CHF)	4.5 kW/m² (Mezzano)
	Reaction to fire; floors smoke value	7% min (Mezzano)
	BCA group number	Group 3

Installation methods	Fully bonded	Yes
	Nailed	No
	Floated	Yes
	Over underfloor heating	No
	Wall / ceiling cladding	Yes

Disclaimer	Uniqueness in colour, grain, knots and natural features is to be expected. Extended lead times may apply depending on material availability.
------------	--

